

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEKD60041MW-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		6200 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	下面開放
反射面	白色



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	665		
10°	688		
20°	671		
30°	528		
40°	259		
50°	104		
60°	38		
70°	7		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		81	74	70	67	64	62	79	74	69	66	63	61	68	65	62	61	62	61	58	56			
0.80		93	85	83	78	77	73	91	84	82	77	76	73	80	76	75	73	74	72	69	68			
1.00		98	88	89	82	82	78	96	87	87	82	81	78	85	81	80	77	78	76	73	72			
1.25		104	92	95	87	88	83	102	91	93	86	87	82	90	85	85	82	83	81	78	77			
1.50		108	95	99	90	93	86	105	94	97	89	92	86	94	88	89	85	87	84	81	80			
2.00		114	99	106	95	100	92	110	98	104	94	99	91	100	92	95	90	92	89	87	85			
2.50		117	101	110	97	105	94	113	99	107	96	103	94	103	95	99	93	95	91	89	88			
3.00		119	102	113	99	108	97	115	101	110	98	106	96	105	96	101	94	97	93	91	90			
4.00		122	104	117	101	113	99	118	102	114	100	110	99	108	99	105	97	100	96	94	92			
5.00		124	105	120	103	116	101	119	103	116	102	113	100	109	100	107	99	102	97	95	93			
10.00		127	106	125	105	123	105	123	105	121	104	119	104	113	102	112	102	106	100	98	96			

