

東芝照明器具配光データシート

名 称	LED高天井照明器具	良	0.83		
形 名	BCP500J_100	中	0.80		
光 源	LED	否	0.76		
形 名	—	効 率	F 0%	最大取付間隔	フィリップスブランド (銘板形名) : BCP500 G4 LED100/850 PSU S-MB JP M
光 束	10000 lm × 1		F 100%		
			F 100%		
前 面	ガラス (クリアー)	器具	光束	A-A	1.2 H
反射面	レンズ		10000 lm	B-B	1.2 H

光度 (cd/1000lm)				反 射 率 (%)	天井											
θ \ φ	A-A	B-B	C-C		80				70				50			
0°	490			壁	70	50	30		70	50	30		50	30	30	10
10°	484			床	30	10	30	10	30	10	30	10	30	10	30	10
20°	461			室指数	照 明 率 (×0.01)											
30°	409			0.60	71	66	59	56	51	49	70	64	58	55	51	49
40°	316			0.80	84	76	72	68	64	62	82	75	71	67	64	61
50°	202			1.00	91	82	79	73	71	68	89	80	78	73	70	67
60°	80			1.25	98	87	87	80	79	74	95	86	85	79	78	74
70°	24			1.50	103	90	92	84	85	79	100	89	90	83	84	78
80°	7			2.00	110	95	101	90	94	86	106	94	99	89	93	85
90°	0			2.50	114	98	106	94	100	90	110	97	103	93	98	89
100°	0			3.00	116	100	110	96	104	93	113	99	107	95	102	92
110°	0			4.00	120	102	115	99	110	97	116	101	111	98	107	96
120°	0			5.00	122	103	118	101	113	99	118	102	114	100	110	98
130°	0			10.00	126	106	124	104	121	103	122	104	120	103	117	102
140°	0															
150°	0															
160°	0															
170°	0															
180°	0															

