

東芝照明器具配光データシート

名 称	LED高天井照明器具	良	0.83		
形 名	BCP500J_190	保守率	0.80		
		否	0.76		
光源	名称	LED	効 率		最大取付間隔 A-A 1.2 H B-B 1.2 H
	形 名	—			
	光束	19000 lm × 1			
前 面	ガラス (クリアー)	器具光束	19000 lm	備 考	フィリップスブランド (銘板形名) : BCP500 G4 LED190/850 PSU S-MB JP M
反射面	レンズ				

光度 (cd/1000lm)				反射率 (%)	天井				80						70						50						30			20		0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10		0							
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0				
室指数				照 明 率 (×0.01)																													
0°				0.60	71	66	59	56	51	49	70	64	58	55	51	49	56	54	50	49	49	48	45	43									
10°				0.80	84	76	72	68	64	62	82	75	71	67	64	61	69	66	63	61	62	60	56	55									
20°				1.00	91	82	79	73	71	68	88	80	78	73	70	67	75	71	69	67	68	66	62	61									
30°				1.25	98	87	87	80	79	74	95	86	85	79	78	74	82	77	76	73	74	72	69	67									
40°				1.50	102	90	92	84	85	79	99	89	90	83	84	78	87	81	81	77	79	76	73	71									
50°				2.00	110	95	101	90	94	86	106	94	99	89	92	85	94	88	89	84	86	83	80	78									
60°				2.50	113	98	106	93	100	90	110	97	103	93	98	89	98	91	94	88	90	86	84	82									
70°				3.00	116	100	110	96	104	93	112	98	107	95	102	92	101	93	97	90	93	89	87	85									
80°				4.00	120	102	114	99	110	96	116	101	111	98	107	96	105	96	102	94	97	92	90	88									
90°				5.00	122	103	117	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	90									
100°				10.00	126	106	124	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	96	95									
110°																																	
120°																																	
130°																																	
140°																																	
150°																																	
160°																																	
170°																																	
180°																																	

