


東芝照明器具配光データシート

名 称	LEDシーリングライト
形 名	LEDH8103A02-LC

効 率	F 	3 %
	F 	97 %
	F 	100 %
器具光束		3800 lm

保守率	良	0.63
	中	0.60
	否	0.56



前 面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	320	319	319
10°	316	314	315
20°	299	297	298
30°	273	269	271
40°	238	234	236
50°	196	192	194
60°	150	145	147
70°	101	97	99
80°	55	51	54
90°	19	18	22
100°	10	10	9
110°	6	6	5
120°	4	4	3
130°	2	2	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	1	2	1
180°	2	2	1

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		61	56	47	44	38	37	59	55	46	44	37	36	44	42	37	36	36	35	31	29			
0.80		73	66	59	55	49	47	71	65	57	54	48	47	55	52	47	46	46	45	40	38			
1.00		80	72	66	61	56	53	77	70	64	60	55	53	61	58	54	52	52	51	46	44			
1.25		88	78	74	68	65	61	85	76	72	67	63	60	69	65	61	58	59	57	52	50			
1.50		93	82	80	73	71	66	89	80	78	71	69	65	74	69	66	63	64	62	57	55			
2.00		101	88	90	80	81	74	97	86	87	79	79	73	82	76	76	71	72	70	65	63			
2.50		106	91	96	85	88	79	102	89	93	83	85	78	87	81	81	76	77	74	70	68			
3.00		110	94	101	88	93	83	105	92	97	87	91	82	91	84	86	80	81	78	74	71			
4.00		114	97	107	93	101	88	110	95	103	91	98	87	96	88	92	85	87	83	79	77			
5.00		117	99	111	95	105	92	112	97	107	94	102	90	100	91	96	88	90	86	83	80			
10.00		123	103	120	101	116	99	118	101	115	99	112	98	107	97	105	95	98	92	90	87			

