

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDD87052L (W) -LS

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		510 lm

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

前 面	
反射面	



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	344		
10°	338		
20°	321		
30°	294		
40°	258		
50°	213		
60°	160		
70°	101		
80°	25		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	1		
150°	1		
160°	1		
170°	1		
180°	1		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		62	57	48	46	40	38	61	56	47	45	39	38	46	44	38	38	38	37	33	31		
0.80		75	68	61	57	51	49	73	66	59	56	51	49	57	55	50	48	49	48	43	41		
1.00		82	74	68	63	59	56	80	72	67	62	58	55	64	61	57	55	55	54	49	47		
1.25		90	80	77	70	67	63	87	78	75	70	66	63	72	68	64	62	63	61	56	54		
1.50		95	84	83	75	74	68	92	82	81	74	72	68	77	72	70	67	68	66	61	59		
2.00		104	90	93	83	85	77	100	89	90	82	83	76	86	80	80	75	77	74	70	68		
2.50		108	93	99	87	91	82	105	92	96	86	89	81	91	84	85	80	82	79	75	73		
3.00		112	96	104	91	97	86	108	94	101	90	94	85	95	87	90	84	86	82	79	77		
4.00		117	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82		
5.00		119	101	114	98	109	94	115	99	110	96	106	94	103	94	100	92	95	90	87	85		
10.00		125	105	122	103	119	101	120	103	118	102	115	100	110	99	108	98	102	96	94	92		

