

東芝照明器具配光データシート

名 称	LEDダウンライト
形 名	LEDD-10047N-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	14800 lm

保 守 率	良	0.83
	中	0.81
	否	0.77

前 面	下面開放
反射面	鏡面処理

最大取付間隔	
A-A	0.9 H
B-B	0.9 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	806		
10°	799		
20°	597		
30°	401		
40°	292		
50°	163		
60°	46		
70°	0		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30						20					
	壁	70						50						30						10						0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数		固有照明率 (×0.01)																													
0.60	79	73	68	64	61	59	77	72	67	64	61	59	66	63	60	59	59	58	55	54											
0.80	91	83	81	76	74	71	90	82	80	75	74	71	78	74	72	70	71	70	67	65											
1.00	97	87	87	81	80	76	95	86	86	80	79	75	83	79	78	75	76	74	71	70											
1.25	103	91	93	86	86	81	100	90	92	85	85	81	89	84	83	80	81	79	76	75											
1.50	107	94	98	89	91	85	104	93	96	88	90	84	93	87	88	83	85	82	80	78											
2.00	113	98	105	94	99	91	110	97	103	93	97	90	99	92	94	89	91	88	85	84											
2.50	116	100	109	97	104	94	113	99	107	96	102	93	102	94	98	92	94	90	88	87											
3.00	119	102	113	99	108	96	115	100	110	98	105	95	104	96	101	94	97	93	90	89											
4.00	122	103	117	101	113	99	118	102	114	100	110	98	107	98	105	97	100	95	93	92											
5.00	123	104	119	103	116	101	119	103	116	102	113	100	109	100	107	98	102	97	95	93											
10.00	127	106	125	106	123	105	123	105	121	104	119	104	113	102	112	102	106	100	98	96											

