

東芝照明器具配光データシート

名 称	LEDダウンライト
形 名	LEDD-20037N-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	19600 lm

保 守 率	良	0.83
	中	0.81
	否	0.77

前 面	下面開放
反射面	鏡面処理

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	725		
10°	690		
20°	577		
30°	399		
40°	290		
50°	179		
60°	64		
70°	2		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30						20					
	壁	70						50						30						10						0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数		固有照明率 (×0.01)																													
0.60	77	71	65	62	58	56	75	70	64	61	58	56	63	61	57	56	56	55	52	51											
0.80	89	81	78	74	71	68	87	80	77	73	71	68	75	72	70	68	69	67	64	62											
1.00	95	86	85	79	77	74	93	84	83	78	77	73	81	77	75	72	74	72	69	67											
1.25	102	90	92	84	84	79	99	89	90	83	83	79	87	82	81	78	79	77	74	73											
1.50	106	93	96	88	90	83	103	92	94	87	88	83	91	85	86	82	84	81	78	76											
2.00	112	97	104	93	98	89	109	96	102	92	96	89	97	91	93	88	90	87	84	82											
2.50	115	100	109	96	103	93	112	98	106	95	101	92	101	93	97	91	93	89	87	86											
3.00	118	101	112	98	107	95	114	100	109	97	104	94	103	95	100	93	96	92	89	88											
4.00	121	103	116	101	112	98	117	102	113	100	109	98	107	98	104	96	99	95	93	91											
5.00	123	104	119	102	115	100	119	103	115	101	112	99	109	99	106	98	101	96	94	93											
10.00	127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	101	105	99	98	96											

