

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEDL-12402W-LS9

効 率	F 	4 %
	F 	96 %
	F 	100 %
	器具 光束	2430 lm

保守 率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	



備考	
----	--

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0																									
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0																											
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0																									
						固有照明率 (×0.01)																																														
0°	362	362	362	室指数	0.60																								63	58	49	47	41	40	61	57	48	46	40	39	47	45	39	38	38	33	32					
10°	354	354	355		0.80																								75	68	62	58	53	50	73	67	60	57	52	50	58	55	50	49	49	48	43	41				
20°	333	333	333		1.00																								82	74	69	64	60	57	80	72	67	63	59	56	64	61	57	55	55	54	49	47				
30°	297	297	297		1.25																								90	80	77	71	68	64	87	78	75	69	67	63	71	67	64	61	62	60	56	53				
40°	247	248	249		1.50																								95	84	83	75	74	68	91	82	80	74	72	68	76	71	69	66	67	65	60	58				
50°	192	190	192		2.00																								103	90	92	83	84	77	99	88	90	81	82	76	84	79	78	74	75	72	68	65				
60°	136	132	136		2.50																								107	93	98	87	90	82	103	91	95	85	88	80	89	82	84	78	80	76	73	70				
70°	86	77	83		3.00																								111	95	103	90	96	85	107	93	99	88	93	84	93	86	88	82	83	80	76	74				
80°	44	29	37		4.00																								115	98	109	94	103	90	111	96	105	92	99	89	98	89	94	87	88	84	81	78				
90°	20	2	13		5.00																								118	100	112	96	107	93	113	98	108	95	104	92	101	92	97	89	91	87	84	81				
100°	19	2	12		10.00																								124	103	121	102	117	100	119	102	116	100	113	98	107	97	105	96	98	93	91	88				
110°	15	1	8																																																	
120°	11	1	6																																																	
130°	5	1	6																																																	
140°	4	1	5																																																	
150°	3	2	3																																																	
160°	3	2	2																																																	
170°	2	2	2																																																	
180°	2	2	2																																																	

