

東芝照明器具配光データシート

名 称	LEDダウンライト
形 名	LEKD75053NV-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		7700 lm

保守率	良	0.76
	中	0.72
	否	0.64

最大取付間隔	
A-A	0.7 H
B-B	0.7 H

前 面	下面開放
反射面	梨地処理



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	1394		
10°	1242		
20°	816		
30°	443		
40°	183		
50°	36		
60°	16		
70°	6		
80°	1		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60	91 84 82 78 77 74 90 83 81 78 76 74 80 77 75 74 75 73 71 70																							
0.80	102 92 94 88 88 85 100 92 93 87 88 84 91 87 86 84 85 83 82 81																							
1.00	105 94 97 90 91 87 103 94 96 89 91 86 93 89 89 86 88 85 83 82																							
1.25	109 97 101 93 95 89 106 96 99 92 94 89 96 91 92 88 90 88 85 84																							
1.50	112 98 104 95 99 92 109 97 102 94 97 91 99 93 95 90 93 90 88 86																							
2.00	116 101 109 98 104 95 113 100 107 97 102 95 103 96 99 93 96 92 91 89																							
2.50	118 102 113 100 108 97 115 101 110 99 106 97 105 97 102 95 98 94 92 91																							
3.00	120 103 115 101 111 99 117 102 112 100 108 98 107 98 104 97 100 95 94 92																							
4.00	123 105 119 103 115 101 119 104 116 102 112 100 109 100 107 99 102 97 96 94																							
5.00	125 105 121 104 118 103 121 104 118 103 115 102 111 101 109 100 104 99 97 96																							
10.00	128 107 127 107 125 106 124 106 122 106 121 105 115 104 114 103 107 101 100 98																							

