

■ 東芝照明器具配光データシート


名 称	L E D照明器具
形 名	LEKD75981LV-LD9

効 率	F 	0 %
	F 	1 0 0 %
	F 	1 0 0 %
	器具 光束	7 2 0 0 lm

保守率	良	0.76
	中	0.72
	否	0.64

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

前 面	下面開放
反射面	梨地処理



光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	754		
10°	716		
20°	624		
30°	483		
40°	294		
50°	131		
60°	30		
70°	2		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		80	74	69	66	62	60	78	73	68	65	62	60	67	64	61	60	61	59	56	55			
0.80		93	84	82	77	76	72	91	83	81	77	75	72	79	76	74	72	73	71	68	67			
1.00		98	88	88	82	81	77	96	87	87	81	80	77	84	80	79	76	77	75	73	71			
1.25		104	92	94	87	88	82	101	91	93	86	87	82	90	85	85	81	83	80	78	76			
1.50		108	95	99	90	92	86	105	94	97	89	91	85	94	88	89	84	86	84	81	80			
2.00		113	99	106	95	100	91	110	98	104	94	98	91	99	92	95	90	92	89	86	85			
2.50		117	101	110	97	105	94	113	99	107	96	103	94	102	95	99	92	95	91	89	88			
3.00		119	102	113	99	108	97	115	101	110	98	106	96	105	96	101	94	97	93	91	89			
4.00		122	104	117	101	113	99	118	102	114	100	110	99	108	99	105	97	100	95	94	92			
5.00		124	105	120	103	116	101	119	103	116	102	113	100	109	100	107	98	102	97	95	93			
10.00		127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	102	105	100	98	96			

