

■ 東芝照明器具配光データシート



名 称	東芝LED照明器具
形 名	LEER-42302F-BD9+LEEM-40404N-HG

効 率	F 	2 %
	F 	98 %
	F 	100 %
	器具光	4000 lm

保守率	良	0.88
	中	0.86
	否	0.81

最大取付間隔		
A-A	1.3	H
B-B	1.2	H

前 面	カバー（乳白）
反射面	塗装（白）

	θ	
	ϕ	

LEER-42302F-BD9+LEEM-40404N-HG

備考

光度(cd/1000lm)				反射率 (%)	天井	80						70						50				30		20	0						
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70		50		30		50		30		30		10	0			
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
	固有照明率(×0.01)																														
室指数																															
0°				0.60	60	56	46	44	37	36	59	54	45	43	37	36	43	42	36	35	35	34	30	28							
10°				0.80	72	66	58	54	48	46	70	64	56	53	47	46	54	52	46	45	45	44	39	37							
20°				1.00	79	71	65	60	55	52	77	70	63	59	54	52	61	58	53	51	51	50	45	43							
30°				1.25	87	77	73	67	63	59	84	76	71	66	62	59	68	64	60	58	58	56	52	49							
40°				1.50	92	81	79	72	69	64	89	79	77	71	68	64	73	68	66	62	63	61	56	54							
50°				2.00	101	88	89	80	80	73	97	86	86	78	78	72	82	76	75	71	72	69	65	62							
60°				2.50	105	91	95	84	87	78	101	89	92	83	84	77	87	80	81	75	77	74	70	67							
70°				3.00	109	94	100	87	92	82	105	92	97	86	90	81	91	84	85	79	81	78	74	71							
80°				4.00	114	97	106	92	100	88	110	95	103	91	97	86	96	88	91	84	87	83	79	77							
90°				5.00	117	99	110	95	104	91	112	97	107	93	101	90	100	91	95	88	90	86	82	80							
100°				10.00	123	103	120	101	116	99	118	102	115	99	112	97	107	97	105	95	98	93	90	88							
110°																															
120°																															
130°																															
140°																															
150°																															
160°																															
170°																															
180°																															

