

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEDD-18003F-BD9 + LEEU-2505L2-03

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	1910 lm

保守 率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

前 面	下面開放
反射面	白色



備考	LEDD-18003F-BD9+LEEU-2505L2-03
----	--------------------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	790		
10°	702		
20°	518		
30°	399		
40°	277		
50°	160		
60°	78		
70°	23		
80°	8		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射 率 (%)	天井	80						70						50						30						20					
	壁	70						50						30						10						0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数		固有照明率 (×0.01)																													
0.60		76	70	64	60	57	55	74	69	63	60	56	55	62	59	55	54	55	54	50	49										
0.80		88	80	77	72	69	66	86	79	76	71	69	66	74	70	68	66	66	65	62	60										
1.00		94	84	83	77	75	71	91	83	81	76	75	71	79	75	73	70	72	70	66	65										
1.25		100	89	90	82	82	77	97	88	88	81	81	77	85	80	79	76	77	75	72	70										
1.50		104	92	94	86	87	81	101	91	93	85	86	81	89	83	84	80	81	79	76	74										
2.00		111	96	102	92	96	88	107	95	100	91	94	87	96	89	91	86	88	85	82	80										
2.50		114	99	107	95	101	91	111	97	104	94	99	90	99	92	95	89	91	88	85	84										
3.00		117	100	111	97	105	94	113	99	108	96	103	93	102	94	98	92	94	90	88	86										
4.00		121	102	115	100	111	97	116	101	112	99	108	96	106	97	103	95	98	93	91	89										
5.00		123	104	118	101	114	99	118	102	115	100	111	98	108	98	105	97	100	95	93	91										
10.00		127	106	124	105	122	104	122	105	120	104	118	103	113	102	111	101	105	99	97	96										

