



■ 東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.69	θ  ϕ 		
形 名		LEDL-15903L-LD9			中	0.67			
					否	0.63			
光源	名称	LEDランプ		効 率	F 	7 %		最大取付間隔	
	形 名	—			F 	93 %			A-A
	光束	3120 lm × 1			F 	100 %	B-B		1.2 H
前 面		カバー（フロスト）		器具 光束	3120 lm	備考			
反射面									

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			50			30			30		10	0				
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
				室指数	照 明 率 (×0.01)																							
0°	347	347	347	0.60	62	57	48	46	40	38	60	55	47	45	39	38	45	43	38	37	37	36	32	30				
10°	337	327	328	0.80	74	67	60	56	51	49	71	65	58	55	50	48	56	53	48	47	47	46	41	39				
20°	313	313	311	1.00	81	73	67	62	58	55	78	71	65	61	57	54	62	59	55	53	53	51	47	44				
30°	275	288	276	1.25	88	79	75	69	66	62	85	76	73	68	65	61	69	65	62	59	59	58	53	50				
40°	227	253	234	1.50	93	82	81	74	72	67	90	80	79	72	70	66	74	69	67	64	64	62	57	55				
50°	175	197	184	2.00	101	88	91	81	82	75	97	86	88	79	80	74	82	76	76	72	72	69	65	62				
60°	125	135	133	2.50	106	91	96	85	89	80	102	89	93	84	86	79	87	80	81	76	77	74	70	67				
70°	81	84	86	3.00	110	94	101	88	94	84	105	92	97	87	91	82	91	83	86	80	81	77	73	70				
80°	49	37	47	4.00	114	97	107	93	101	89	109	95	103	91	97	87	96	87	91	84	86	82	78	75				
90°	25	11	19	5.00	117	99	111	95	105	92	112	97	106	93	102	90	99	90	95	87	89	84	81	78				
100°	14	11	11	10.00	123	103	119	101	116	99	117	101	114	99	111	97	105	95	103	94	96	90	88	85				
110°	12	11	11																									
120°	11	11	11																									
130°	12	6	10																									
140°	12	7	10																									
150°	11	7	9																									
160°	5	2	3																									
170°	3	3	3																									
180°	0	0	0																									

