

東芝照明器具配光データシート

名 称	LEDライン器具	良	0.69		θ
形 名	LEDL-12903N-LD9	中	0.67		
		否	0.63		
光源	名 称	-	F	4 %	ϕ
	形 名	-	F	96 %	
	光束	2580 lm × 1	F	100 %	
前 面	カバー (フロスト)	器具	2580 lm	最大取付間隔	備考
反射面		光束		A-A 1.2 H	
				B-B 1.3 H	

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
						照 明 率 (×0.01)																					
0°	349	349	349	室指数																							
10°	343	344	343	0.60	63	58	49	46	40	39	61	56	48	46	40	39	46	44	39	38	38	37	33	31			
20°	322	331	325	0.80	75	68	61	57	52	50	73	66	60	56	51	49	57	55	50	48	48	47	43	41			
30°	289	298	294	1.00	82	74	68	63	59	56	79	72	67	62	58	55	64	60	56	54	55	53	48	46			
40°	244	251	248	1.25	90	80	77	70	67	63	86	78	75	69	66	62	71	67	64	61	61	60	55	53			
50°	191	192	194	1.50	95	83	82	75	73	68	91	81	80	73	72	67	76	71	69	66	66	64	60	57			
60°	138	131	138	2.00	103	89	92	82	84	76	99	87	89	81	82	75	84	78	78	73	74	72	68	65			
70°	90	75	87	2.50	107	93	98	86	90	81	103	91	95	85	88	80	89	82	83	78	79	76	72	70			
80°	53	27	45	3.00	111	95	102	90	95	85	106	93	99	88	92	84	93	85	88	82	83	80	76	73			
90°	25	1	16	4.00	115	98	108	94	102	90	111	96	105	92	99	89	98	89	93	86	88	84	81	78			
100°	11	2	7	5.00	118	100	112	96	107	93	113	98	108	95	103	92	101	92	97	89	91	87	84	81			
110°	8	3	6	10.00	124	104	121	102	117	100	119	102	116	100	113	98	107	97	105	96	98	93	91	88			
120°	7	3	6																								
130°	7	2	6																								
140°	7	2	5																								
150°	6	2	5																								
160°	4	3	3																								
170°	3	3	2																								
180°	2	2	2																								

