



東芝照明器具配光データシート

名 称	LEDライン器具	良	0.69		θ 
形 名	LEDL-09903N-LD9	中	0.67		
		否	0.63		
光源	名称	-	F 	4 %	ϕ 
	形名	-	F 	96 %	
	光束	1960 lm × 1	F 	100 %	
前 面	カバー (フロスト)	器具光束	1960 lm	最大取付間隔	備考
反射面				A-A 1.2 H B-B 1.2 H	

光度 (cd/1000lm)				天井	80			70			50			30			20			0
$\theta \setminus \phi$	A-A	B-B	C-C	壁	70	50	30	70	50	30	50	30	30	30	10	0	10	0	10	0
0°	350	350	350	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
10°	344	344	344	室指数	照 明 率 (×0.01)															
20°	324	324	324	0.60	63	58	49	46	40	39	61	56	48	45	40	39	46	44	39	38
30°	291	290	291	0.80	75	68	61	57	52	50	72	66	59	56	51	49	57	54	50	48
40°	248	243	246	1.00	82	73	68	63	59	56	79	72	67	62	58	55	63	60	56	54
50°	196	186	192	1.25	89	79	76	70	67	63	86	78	74	69	66	62	71	67	63	61
60°	143	127	137	1.50	94	83	82	74	73	68	91	81	80	73	71	67	76	71	69	65
70°	95	73	87	2.00	103	89	92	82	83	76	99	87	89	81	81	75	84	78	78	73
80°	56	26	45	2.50	107	92	97	86	90	81	103	90	94	85	87	80	89	82	83	78
90°	28	1	16	3.00	111	95	102	89	95	85	106	93	99	88	92	83	92	85	87	81
100°	13	2	7	4.00	115	98	108	94	102	90	110	96	104	92	99	88	97	89	93	86
110°	9	2	6	5.00	118	100	112	96	107	93	113	98	108	94	103	91	100	92	97	89
120°	8	3	6	10.00	124	103	120	101	117	100	119	102	116	100	113	98	107	97	105	95
130°	8	3	6																	
140°	8	2	6																	
150°	6	3	5																	
160°	5	3	3																	
170°	3	3	2																	
180°	2	2	2																	

