

東芝照明器具配光データシート

名 称	LEDライン器具	良	0.69		θ
形 名	LEDL-09903L-LD9	中	0.67		
		否	0.63		
光源	名称 - 形名 - 光束 1750 lm × 1	効 率	F 4 % F 96 % F 100 % 器具光束 1750 lm	最大取付間隔	ϕ
前 面	カバー (フロスト)			A-A 1.2 H	
反射面				B-B 1.2 H	
				備考	

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
				室指数	照 明 率 (×0.01)																							
0°		350	350	350	0.60	63	58	49	46	40	39	61	56	48	45	40	39	46	44	39	38	38	37	33	31			
10°		344	344	344	0.80	75	68	61	57	52	50	72	66	59	56	51	49	57	54	50	48	48	47	43	40			
20°		324	324	324	1.00	82	73	68	63	59	56	79	72	67	62	58	55	63	60	56	54	54	53	48	46			
30°		291	290	291	1.25	89	79	76	70	67	63	86	78	74	69	66	62	71	67	63	61	61	59	55	52			
40°		248	243	246	1.50	94	83	82	74	73	68	91	81	80	73	71	67	76	71	69	65	66	64	59	57			
50°		196	186	192	2.00	103	89	92	82	83	76	99	87	89	81	81	75	84	78	78	73	74	71	67	65			
60°		143	127	137	2.50	107	92	97	86	90	81	103	90	94	85	87	80	89	82	83	78	79	76	72	69			
70°		95	73	87	3.00	111	95	102	89	95	85	106	93	99	88	92	83	92	85	87	81	83	79	76	73			
80°		56	26	45	4.00	115	98	108	94	102	90	110	96	104	92	99	88	97	89	93	86	88	84	80	78			
90°		28	1	16	5.00	118	100	112	96	107	93	113	98	108	94	103	91	100	92	97	89	91	87	83	81			
100°		13	2	7	10.00	124	103	120	101	117	100	119	102	116	100	113	98	107	97	105	95	98	93	90	88			
110°		9	2	6																								
120°		8	3	6																								
130°		8	3	6																								
140°		8	2	6																								
150°		6	3	5																								
160°		5	3	3																								
170°		3	3	2																								
180°		2	2	2																								

