

東芝照明器具配光データシート

名 称		LEDライン器具		良	0.69		θ 			
形 名		LEDL-06903N-LD9						中	0.67	ϕ
光 源	名 称	-		保守率	否	0.63				
	形 名	-								
	光 束	1290 lm x 1								
前 面	カバー（フロスト）		効 率	F	4 %	最大取付間隔	備考			
				F	96 %			A-A	1.2 H	
				F	100 %			B-B	1.2 H	
				器具 光 束	1290 lm					
反射面										

光度 (cd/1000lm)				天井	80			70			50			30			20			0
$\theta \setminus \phi$	A-A	B-B	C-C	壁	70	50	30	70	50	30	50	30	30	30	10	0	30	10	0	0
0°	352	352	352	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
10°	346	345	346	室指数	照 明 率 (×0.01)															
20°	326	326	326	0.60	63	58	49	46	40	39	61	56	48	46	40	39	46	44	39	38
30°	293	293	293	0.80	75	68	61	57	52	50	73	66	60	56	51	49	57	55	50	48
40°	248	244	247	1.00	82	74	68	63	59	56	79	72	67	62	58	55	64	60	56	54
50°	196	187	193	1.25	90	80	77	70	67	63	86	78	75	69	66	62	71	67	64	61
60°	142	128	137	1.50	95	83	82	75	73	68	91	81	80	73	72	67	76	71	69	66
70°	94	73	86	2.00	103	89	92	82	83	76	99	87	89	81	81	75	84	78	78	73
80°	55	26	45	2.50	107	93	98	86	90	81	103	91	95	85	88	80	89	82	83	78
90°	27	1	16	3.00	111	95	102	90	95	85	106	93	99	88	92	84	93	85	87	82
100°	12	1	7	4.00	115	98	108	94	102	90	111	96	104	92	99	89	98	89	93	86
110°	8	1	6	5.00	118	100	112	96	107	93	113	98	108	95	103	92	101	92	97	89
120°	8	2	6	10.00	124	103	120	102	117	100	119	102	116	100	113	98	107	97	105	95
130°	8	2	6																	
140°	8	2	6																	
150°	7	2	5																	
160°	5	2	3																	
170°	2	2	2																	
180°	2	2	2																	

