



東芝照明器具配光データシート

名 称		LEDライン器具		保守率	良	0.69	θ ϕ		
形 名		LEDL-06903L-LD9			中	0.67			
					否	0.63			
光源	名称	-		効 率	F 	4 %		最大取付間隔	
	形名	-			F 	96 %			A-A
	光束	1200 lm × 1			F 	100 %	B-B		1.2 H
前 面		カバー（フロスト）			器具 光束	1200 lm	備考		
反射面									

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
				室指数	照 明 率 (×0.01)																							
0°		352	352	352	0.60	63	58	49	46	40	39	61	56	48	46	40	39	46	44	39	38	38	37	33	31			
10°		346	345	346	0.80	75	68	61	57	52	50	73	66	60	56	51	49	57	55	50	48	48	47	43	41			
20°		326	326	326	1.00	82	74	68	63	59	56	79	72	67	62	58	55	64	60	56	54	54	53	48	46			
30°		293	293	293	1.25	90	80	77	70	67	63	86	78	75	69	66	62	71	67	64	61	61	60	55	53			
40°		248	244	247	1.50	95	83	82	75	73	68	91	81	80	73	72	67	76	71	69	66	66	64	60	57			
50°		196	187	193	2.00	103	89	92	82	83	76	99	87	89	81	81	75	84	78	78	73	74	72	67	65			
60°		142	128	137	2.50	107	93	98	86	90	81	103	91	95	85	88	80	89	82	83	78	79	76	72	70			
70°		94	73	86	3.00	111	95	102	90	95	85	106	93	99	88	92	84	93	85	87	82	83	79	76	73			
80°		55	26	45	4.00	115	98	108	94	102	90	111	96	104	92	99	89	98	89	93	86	88	84	81	78			
90°		27	1	16	5.00	118	100	112	96	107	93	113	98	108	95	103	92	101	92	97	89	91	87	84	81			
100°		12	1	7	10.00	124	103	120	102	117	100	119	102	116	100	113	98	107	97	105	95	98	93	90	88			
110°		8	1	6																								
120°		8	2	6																								
130°		8	2	6																								
140°		8	2	6																								
150°		7	2	5																								
160°		5	2	3																								
170°		2	2	2																								
180°		2	2	2																								

