

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDD87156L (W) -LS1

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		550 lm

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	387		
10°	379		
20°	358		
30°	324		
40°	277		
50°	218		
60°	147		
70°	73		
80°	14		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		65	60	51	48	43	41	63	58	50	48	42	41	49	47	42	41	41	40	36	34			
0.80		78	70	64	60	55	53	75	69	63	59	55	52	61	58	53	52	52	51	47	45			
1.00		85	76	72	66	63	59	82	75	70	66	62	59	68	64	60	58	59	57	53	51			
1.25		93	82	80	73	71	67	90	81	78	72	70	66	75	71	68	65	66	64	60	58			
1.50		98	86	86	78	77	72	94	84	84	77	76	71	80	75	74	70	71	69	65	63			
2.00		106	92	96	85	88	80	102	90	93	84	86	79	89	83	83	78	80	77	73	71			
2.50		110	95	101	90	94	85	106	94	99	89	92	84	94	87	88	83	85	81	78	76			
3.00		114	97	106	93	99	89	110	96	103	92	97	88	97	90	93	86	89	85	82	80			
4.00		118	100	112	97	106	93	114	99	108	96	103	92	102	93	98	91	94	89	86	85			
5.00		120	102	115	99	110	96	116	101	112	98	107	95	105	96	102	93	97	92	89	87			
10.00		126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93			

