

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDD87156WW (W) -LS1

効 率	F 	0 %
	F 	101 %
	F 	101 %
器具光束		600 lm

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	385		
10°	377		
20°	356		
30°	323		
40°	278		
50°	219		
60°	149		
70°	77		
80°	16		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30	20	0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	固有照明率 (×0.01)																					
0.60	65	60	51	49	43	41	63	59	50	48	42	41	49	47	42	41	41	40	36	34		
0.80	78	71	64	60	55	53	76	69	63	59	55	52	61	58	53	52	52	51	47	45		
1.00	85	76	72	67	63	59	83	75	70	66	62	59	68	64	60	58	59	57	53	51		
1.25	93	83	80	74	71	67	90	81	79	73	70	66	75	71	68	65	66	64	60	58		
1.50	98	86	86	78	77	72	95	85	84	77	76	71	81	75	74	70	72	69	65	63		
2.00	106	93	96	86	88	80	103	91	94	85	86	80	89	83	83	78	80	77	74	72		
2.50	111	96	102	90	95	85	107	94	99	89	93	85	94	87	89	83	85	82	78	76		
3.00	114	98	106	93	100	89	110	97	103	92	97	88	98	90	93	87	89	85	82	80		
4.00	119	101	112	97	107	94	115	100	109	96	104	93	103	94	99	91	94	90	87	85		
5.00	121	103	116	100	111	97	117	101	112	98	108	96	106	96	102	94	97	92	90	88		
10.00	127	106	124	104	121	103	122	105	120	103	117	102	112	101	110	100	104	98	96	94		

