

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDD87157N (W) -LS1

効 率	F 	0 %
	F 	101 %
	F 	101 %
器具光束		830 lm

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	383		
10°	376		
20°	356		
30°	323		
40°	277		
50°	219		
60°	149		
70°	76		
80°	16		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		65	60	51	48	43	41	63	59	50	48	42	41	49	47	41	41	41	40	36	34		
0.80		78	71	64	60	55	53	76	69	63	59	54	52	61	58	53	52	52	51	47	45		
1.00		85	76	72	66	63	59	82	75	70	66	62	59	68	64	60	58	59	57	53	51		
1.25		93	82	80	73	71	67	90	81	78	73	70	66	75	71	68	65	66	64	60	58		
1.50		98	86	86	78	77	72	95	85	84	77	76	71	80	75	74	70	71	69	65	63		
2.00		106	92	96	86	88	80	103	91	94	85	86	80	89	83	83	78	80	77	73	71		
2.50		111	95	102	90	94	85	107	94	99	89	92	84	94	87	89	83	85	82	78	76		
3.00		114	98	106	93	100	89	110	96	103	92	97	88	98	90	93	86	89	85	82	80		
4.00		119	101	112	97	107	94	114	99	109	96	104	93	102	94	99	91	94	89	87	85		
5.00		121	102	116	99	111	97	117	101	112	98	108	96	105	96	102	94	97	92	90	88		
10.00		127	106	124	104	121	103	122	104	119	103	117	102	112	101	110	100	103	98	96	94		

