

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDD87157WW (W) -LS1

効 率	F 	0 %
	F 	99 %
	F 	99 %
	器具 光束	790 lm

保守 率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	
反射面	塗装 (白)



備 考	
-----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	384		
10°	376		
20°	355		
30°	321		
40°	275		
50°	217		
60°	146		
70°	73		
80°	14		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30	20	0
	壁	70						50						30						10	0	
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数		固有照明率 (×0.01)																				
0.60		64	59	51	48	42	41	63	58	50	48	42	41	48	46	41	40	41	40	36	34	
0.80		77	70	63	59	55	52	75	69	62	59	54	52	60	58	53	51	52	51	46	45	
1.00		84	76	71	66	62	59	82	74	70	65	61	59	67	64	60	58	59	57	53	51	
1.25		92	82	79	73	71	66	89	80	78	72	70	66	75	70	68	65	66	64	60	58	
1.50		97	85	85	77	77	71	94	84	83	76	75	71	80	75	73	70	71	69	65	63	
2.00		105	91	95	85	87	80	102	90	93	84	85	79	88	82	82	78	79	76	73	71	
2.50		109	94	101	89	94	84	106	93	98	88	91	84	93	86	88	82	84	81	77	76	
3.00		113	97	105	92	99	88	109	95	102	91	96	87	97	89	92	86	88	84	81	79	
4.00		117	100	111	96	105	93	113	98	108	95	103	92	101	93	98	90	93	89	86	84	
5.00		120	101	114	98	110	95	115	100	111	97	107	95	104	95	101	93	96	91	89	87	
10.00		125	104	122	103	119	101	120	103	118	102	116	100	110	100	108	98	102	97	95	93	

