

■ 東芝照明器具配光データシート


名 称	LED高天井用照明器具
形 名	LEDJ-15508N-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具光 束	17700 lm

保守率	良	0.83
	中	0.81
	否	0.77

前 面	カバー（透明）
反射面	

最大取付間隔		
A-A	1.3	H
B-B	1.3	H

	 θ 0°
	 ϕ

光度(cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	346		
10°	340		
20°	326		
30°	307		
40°	261		
50°	216		
60°	151		
70°	87		
80°	31		
90°	4		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
	室指数	固有照明率(×0.01)																			
	0.60	63	58	49	46	40	39	61	57	48	46	40	39	46	45	39	38	38	38	33	32
	0.80	75	68	61	57	52	50	73	67	60	57	52	50	58	55	50	49	49	48	44	42
	1.00	83	74	69	64	60	57	80	73	68	63	59	56	65	62	57	55	56	55	50	48
	1.25	90	80	77	71	68	64	88	79	76	70	67	63	72	68	65	62	63	61	57	55
	1.50	96	84	83	76	74	69	92	83	81	75	73	68	78	73	71	67	68	66	62	60
	2.00	104	90	93	83	85	78	100	89	91	82	83	77	86	80	80	76	77	74	70	68
	2.50	108	94	99	88	92	82	105	92	96	86	89	82	91	84	86	80	82	79	75	73
	3.00	112	96	104	91	97	86	108	95	101	90	94	86	95	88	90	84	86	82	79	77
	4.00	117	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82
	5.00	119	101	114	98	109	94	115	99	110	96	105	93	103	94	100	92	95	90	87	85
	10.00	125	104	122	103	119	101	120	103	118	102	115	100	110	99	108	98	102	96	94	92

