

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEDD87155L (W) -LS1

効 率	F 	0 %
	F 	99 %
	F 	99 %
器具光束		760 lm

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

前 面	
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	356		
10°	349		
20°	330		
30°	301		
40°	261		
50°	213		
60°	158		
70°	95		
80°	18		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		63	58	49	46	40	39	61	56	48	46	40	39	46	45	39	38	38	38	33	32			
0.80		75	68	61	57	52	50	73	67	60	57	52	50	58	55	51	49	49	48	44	42			
1.00		82	74	69	64	60	57	80	72	67	63	59	56	65	61	57	55	56	55	50	48			
1.25		90	80	77	71	68	64	87	79	76	70	67	63	72	68	65	62	63	62	57	55			
1.50		95	84	83	76	74	69	92	82	81	75	73	68	78	73	71	67	69	66	62	60			
2.00		104	90	93	83	85	78	100	89	91	82	83	77	86	80	80	76	77	74	71	69			
2.50		108	93	99	88	92	83	105	92	96	86	90	82	91	84	86	80	82	79	76	74			
3.00		112	96	104	91	97	86	108	94	101	90	95	86	95	88	90	84	86	83	79	77			
4.00		116	99	110	95	104	91	112	97	106	94	101	91	100	92	96	89	92	87	85	83			
5.00		119	101	114	97	109	95	115	99	110	96	106	94	103	94	100	92	95	90	88	86			
10.00		125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	102	96	94	92			

