

東芝照明器具配光データシート


名 称	LEDシーリングライト
形 名	LEDH8205B01-LC

効 率	F 	10 %
	F 	90 %
	F 	100 %
器具光束		5500 lm

保守率	良	0.63
	中	0.60
	否	0.56

最大取付間隔		
A-A	1.3	H
B-B	1.3	H

前 面	カバー (乳白)
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	280	280	280
10°	276	275	276
20°	265	264	264
30°	246	244	244
40°	220	217	217
50°	185	182	183
60°	144	141	142
70°	98	96	96
80°	53	52	52
90°	21	23	22
100°	10	11	11
110°	11	12	12
120°	14	15	15
130°	16	16	17
140°	18	18	18
150°	18	18	18
160°	18	18	18
170°	20	21	20
180°	21	21	21

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		59	55	45	43	36	35	57	53	44	42	36	35	41	40	34	33	33	32	28	25		
0.80		71	64	56	53	47	45	68	62	55	52	46	44	52	49	44	43	42	41	37	34		
1.00		78	70	64	59	54	51	75	68	62	58	53	51	58	55	51	49	48	47	42	39		
1.25		86	76	72	66	62	59	82	74	70	65	61	57	65	62	58	55	55	53	48	45		
1.50		91	80	78	71	68	64	87	78	75	69	67	62	70	66	63	60	60	58	53	50		
2.00		99	86	88	78	79	72	95	84	85	77	77	71	79	73	72	68	68	65	61	57		
2.50		104	90	94	83	86	77	99	87	90	81	83	76	84	77	78	73	73	70	65	62		
3.00		108	92	99	86	91	81	103	90	95	84	88	80	87	80	82	76	77	73	69	66		
4.00		112	95	105	91	98	86	107	93	101	89	95	85	93	85	88	81	82	78	74	71		
5.00		115	97	109	93	103	90	110	95	104	91	99	88	96	87	92	84	85	81	77	74		
10.00		121	102	118	99	114	97	116	99	112	97	110	95	103	93	101	91	93	88	85	81		

